



## DRUM SCREEN 1020

### TECHNICAL DATA

#### TRAILER DRUM SCREEN

- Dimension Drum	mm.	2000x1000
- Screen net	mm.	5-100

#### FEEDING: BELT WITH HOPPER

- Length	mm.	2500
- Width	mm.	550
- Hopper capacity	m <sup>3</sup>	1.3
- Loading Height	mm	2000

#### FINE MATERIAL BELT

- Length	mm.	2500
- Width	mm.	500
- Pile height	mm.	1270

#### OVERSIZE MATERIAL BELT

- Length	mm.	1800
- Width	mm.	500
- Pile height	mm.	1585

#### GENERATORE DI CORRENTE

Corrente erogata	kVa	14
	kV	9
	V	380 - 220

### MOTORE ISUZU

- Potenza	kW/Hp	21\28,5
- Consumi	L/h	5,5
- Cilindri	N°	3
- Raffreddamento		acqua

### TANDEM AXLES

-Type		Tridem
-Towbar type		Caravan
-Max speed	Km/h	80

### \*PERFORMANCE

- Production	T/h	60
- Max size	mm.	20
- Standard weight	Kg.	3400

### STANDARD MACHINE

- Assale per la circolazione stradale
- Brushes for clean drum
- Belts for the screening material


### ACCESSORIES

- Rubber Crawled Track
- Remote Control(Only Crawled Version)
- Net With Different Hole
- Dust Dumping System

### DIMENSION At Work Transport

-Lunghezza mm.	6500	6500
-Larghezza mm.	5850	2600
-Altezza mm.	2460	2460

*\*The screen production performance depends by the type of material.*



The technical data and specification hereby supplied are merely indicatives. Komplet reserves the right to modify them without notice



[www.komplet.it](http://www.komplet.it) [info@komplet.it](mailto:info@komplet.it)

+39 071 66 09 823 +39 071 66 11 069

Dealer: